

**DECLARATION OF CONFORMITY**

We General Membrane Spa, manufacturer with premises and production plant in via Venezia 28 - 30022 Ceggia Venice ITALY, tel. +39.0421.322000, fax +39.0421.322800 - export@generalmembrane.it, www.generalmembrane.it, declare on our own responsibility that all the reinforced bitumen sheets for roof waterproofing including on their relevant Conformity Data Sheet the following signs:



are CONFORM to the norm: EN 13707 - Reinforced bitumen sheets for roof waterproofing, March 2005.

**Product Description**

Reinforced bituminous sheets for roof waterproofing.

In terms of the Italian Ministerial Decree n° 65 of March 14th 2003 which sets out "Classification, labelling and packaging preparation in execution of the Directives issued by the Council and by the Commission of the European Community" the product doesn't contain dangerous substances. The bitumen-polymer membranes manufactured by GENERAL MEMBRANE Spa are made by bitumen given from the crude oil distillation and don't contain tar obtained by fossil coal, asbestos, chlorine, regenerated or used oils, are recyclable and they are not a dangerous waste. The bitumen-polymer membrane subject of this declaration are free from the emission of the safety data sheet, of course an informative report for the right product use is available on explicit demand.

**Disposition to which the product is conformable**

Features satisfying the Mandate M102 in the scope of CPD

Essential Features	Points of the norm EN 13707	Levels and/or classes	Notes
Behaviour to the external fire	5.2.5.1	Classes in conformity to EN 13501-5 or that are considered as satisfied	Conformity to the regulation requirements
Reaction to the fire	5.2.5.2	Classes in conformity to EN 13501-1	See note at the point 5.2.5.2 of the EN 13707
Waterproofing	5.2.3	-	Threshold value
Strength resistance	5.2.10	-	
Resistance to roots	5.2.14	-	Only for products used as barrier to the roots on roof gardens
Resistance to static load	5.2.12	-	
Resistance to the impact	5.2.11	-	
Resistance to tearing	5.2.13	-	
Joint strength	5.2.8.1	-	Only for application as single layer mechanically fixed
	5.2.8.2	-	Only for applications as single layer
Durability	5.2.19.1	-	Upper layer with light permanent protection and single layers
	5.2.19.2	-	Upper and single layers without protection of the surface
	5.2.19.3	-	Upper layer with heavy permanent protection, lower and intermediate layer
Pliability	5.2.17	-	
Dangerous substances	5.3	-	See note at the point ZA.1 of the EN 13707

- It means that the mandate doesn't fix any class or level

**Particular conditions applicable for using the product**

Unfavourable weather conditions (rain, snow, humidity), can make difficult and poor-quality the application; if the temperature goes down to +5°C is recommendable to stop the laying, because during the summer season it can create bubbles, detachments or swellings. Similarly during summer, in countries with hot climate and for laying on thermal insulation it would be suitable to avoid the application during the hours with the higher insulation. During winter time is opportune unrolling with care the rolls in order to avoid damages and break the membrane cause of the rigid temperatures.

**Number of certificate for the factory production check**

GB06/69203

Ceggia, July 6<sup>th</sup>, 2006

Dr. Lionello Codognotto  
Chairman General Membrane Spa