

DECLARATION OF CONFORMITY

We General Membrane Spa, manufacturer with premises and production plant in via Venezia 28 - 30022 Ceggia Venice ITALY, tel. +39.0421.322000, fax +39.0421.322800 - export@generalmembrane.it, www.generalmembrane.it, declare on our own responsibility that all the bitumen damp proof sheets including basement tanking sheets including on their relevant Conformity Data Sheet the following signs:



are CONFORM to the norm: EN 13969 – Bitumen damp proof sheets including bitumen basement tanking sheets, March 2005.

Product Description

Bitumen damp proof sheets including bitumen basement tanking sheets.

In terms of the Italian Ministerial Decree n° 65 of March 14th 2003 which sets out "Classification, labelling and packaging preparation in execution of the Directives issued by the Council and by the Commission of the European Community" the product doesn't contain dangerous substances. The bitumen-polymer membranes manufactured by GENERAL MEMBRANE Spa are made by bitumen given from the crude oil distillation and don't contain tar obtained by fossil coal, asbestos, chlorine, regenerated or used oils, are recyclable and they are not a dangerous waste. The bitumen-polymer membrane subject of this declaration are free from the emission of the safety data sheet, of course an informative report for the right product use is available on explicit demand.

Disposition to which the product is conformable

Features satisfying the Mandate M102 in the scope of CPD

Essential Features	Points of the norm EN 13969	Levels and/or classes	Notes
Reaction to the fire	5.14	Classes in conformity EN 13501-1	See note at the point 5.14 of the EN 13969 norm
Waterproofing	5.5	-	Threshold value
Resistance to the impact	5.6	-	
Joint strength	5.10	-	
Pliability	5.8	-	
Strength resistance	5.13	-	
Resistance to static load	5.12	-	
Resistance to tearing	5.9	-	
Durability	5.7.1	-	Waterproofing after artificial ageing
	5.7.2	-	Chemical Resistance
Dangerous substances	5.15	-	See note at the point ZA.1 of the EN 13969 norm

- It means that the mandate doesn't fix any class or level

Particular conditions applicable for using the product

Unfavourable weather conditions (rain, snow, humidity), can make difficult and poor-quality the application; if the temperature goes down to +5°C is recommendable to stop the laying, because during the summer season it can create bubbles, detachments or swellings. Similarly during summer, in countries with hot climate and for laying on thermal insulation it would be suitable to avoid the application during the hours with the higher insulation. During winter time is opportune unrolling with care the rolls in order to avoid damages and break the membrane cause of the rigid temperatures.

Number of certificate for the factory production check

GB06/69203

Ceggia, July 6th, 2006

Dr. Lionello Codognatto
Chairman General Membrane Spa