

STICKY TAPE FINISHES

Adher'Alu M1 [Aluminium adhesive - roll of 75 mm x 50 ml.]

Data sheet

Application temperature :	+ 5°C to + 60°C
Nature of support :	Aluminium
Thickness of support :	40µm
Color :	Paper siliconized 60g/m ²
Nature of adhesive :	Acrylique
Total thickness of the tape :	130µm
Adherence to steel :	6 N/cm
Breaking strength :	26 N/cm
Elongation at break :	9%
Service temperature :	-20°C to +120°C
Fire resistance :	M1 fireproof classified
Width :	75 mm
Length :	50 m
Packaging :	Box of 16 roll
Chuck cardboard :	Ø 78 mm

Recommendations : Must be stored in a cool, dry place away from any direct heat source.

Aluminium tape with its acrylic sticking surface protected by an intermediate silicone.



Bar Code : 3760088086019

This sticky tape is suitable for fire classified products such as DUOREFLEX200.

Adher'XL 5711 [Adhesive - roll of 100 mm x 50 ml.]

Data sheet

Application temperature :	+ 18°C to + 50°C
Nature of support :	polypropylene film
Total thickness of the tape :	32µm
Color :	Silver
Tensile strength :	4,5kg/cm
Elongation at break :	140%
Solvents :	No
Powers of reflection :	80%
Width :	100 mm
Length :	50 m
Packaging :	Box of 18 roll
Chuck cardboard :	Ø 78 mm

Recommendations : Must be stored in a cool, dry place away from any direct heat source.

Metal reinforced coated polypropylene tape with its acrylic sticking.



Bar Code : 3760088086026

Particularly suitable, due its flexibility, for re-jointing of gamuts. It has a high UV resistance and enables the obtention of the best possible reflection, even at joint level.